

Table Of Content

Journal Cover	2
Author[s] Statement	3
Editorial Team	4
Article information	5
Check this article update (crossmark)	5
Check this article impact	5
Cite this article	5
Title page	6
Article Title	6
Author information	6
Abstract	6
Article content	7

ISSN (ONLINE) 2598-9936



INDONESIAN JOURNAL OF INNOVATION STUDIES
PUBLISHED BY
UNIVERSITAS MUHAMMADIYAH SIDOARJO

Originality Statement

The author[s] declare that this article is their own work and to the best of their knowledge it contains no materials previously published or written by another person, or substantial proportions of material which have been accepted for the published of any other published materials, except where due acknowledgement is made in the article. Any contribution made to the research by others, with whom author[s] have work, is explicitly acknowledged in the article.

Conflict of Interest Statement

The author[s] declare that this article was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

Copyright Statement

Copyright © Author(s). This article is published under the Creative Commons Attribution (CC BY 4.0) licence. Anyone may reproduce, distribute, translate and create derivative works of this article (for both commercial and non-commercial purposes), subject to full attribution to the original publication and authors. The full terms of this licence may be seen at <http://creativecommons.org/licenses/by/4.0/legalcode>

Indonesian Journal of Innovation Studies

Vol. 25 No. 1 (2024): January

DOI: 10.21070/ijins.v25i1.1061 . Article type: (Innovation in Industrial Engineering)

EDITORIAL TEAM

Editor in Chief

Dr. Hindarto, Universitas Muhammadiyah Sidoarjo, Indonesia

Managing Editor

Mochammad Tanzil Multazam, Universitas Muhammadiyah Sidoarjo, Indonesia

Editors

Fika Megawati, Universitas Muhammadiyah Sidoarjo, Indonesia

Mahardika Darmawan Kusuma Wardana, Universitas Muhammadiyah Sidoarjo, Indonesia

Wiwit Wahyu Wijayanti, Universitas Muhammadiyah Sidoarjo, Indonesia

Farkhod Abdurakhmonov, Silk Road International Tourism University, Uzbekistan

Bobur Sobirov, Samarkand Institute of Economics and Service, Uzbekistan

Evi Rinata, Universitas Muhammadiyah Sidoarjo, Indonesia

M Faisal Amir, Universitas Muhammadiyah Sidoarjo, Indonesia

Dr. Hana Catur Wahyuni, Universitas Muhammadiyah Sidoarjo, Indonesia

Complete list of editorial team ([link](#))

Complete list of indexing services for this journal ([link](#))

How to submit to this journal ([link](#))

Article information

Check this article update (crossmark)



Check this article impact (*)



Save this article to Mendeley



(*) Time for indexing process is various, depends on indexing database platform

Revitalizing Old Facades: Innovations in Facade System Installation and Preservation

Merevitalisasi Fasad Lama: Inovasi dalam Pemasangan dan Pelestarian Sistem Fasad

Tojiboev Ulugbek, marjonakamilova88@gmail.com, (0)

Samarkand State University of Architecture and Construction, Uzbekistan

Kamilova Marjona, marjonakamilova88@gmail.com, (1)

Samarkand State University of Architecture and Construction, Uzbekistan

⁽¹⁾ Corresponding author

Abstract

This article presents a novel approach to enhancing the aesthetic appeal and longevity of old building facades through the installation of a new facade system. The study aims to improve the appearance of buildings while safeguarding the integrity of existing facades and mitigating various associated challenges. The methodology involves a detailed analysis of the old facade's condition, selection of appropriate materials and technologies for the new system, and implementation strategies for seamless integration. Results indicate significant improvements in building aesthetics, increased durability, and reduced maintenance costs. The implications of this research extend to urban planning, heritage preservation, and sustainable architectural practices, offering valuable insights for architects, engineers, and policymakers globally.

Highlights:

- Facade renovation enhances building aesthetics and preserves historical architecture.
- Innovative materials and technologies ensure long-term sustainability and reduce maintenance costs.
- Global impact: Research findings inform urban development practices, emphasizing heritage preservation and sustainable building strategies.

Keywords: Facade System, Building Renovation, Modernization

Published date: 2024-01-31 00:00:00

Introduction

This renovation option provides for the installation of a new facade system directly on the old facade and is fundamentally different from the "replacement of the facade system", which, as the name implies, provides for the replacement of the old facade with a new facade system. The installation of a new facade system on the old facade of the building is designed to provide the following advantages:

1. reduction of heat loss through the facade of the building and ensuring compliance with modern standards of thermal insulation;
2. improving the appearance of the building;
3. protection of the old facade of the building, including prevention of water leakage;
4. minimal discomfort for residents during renovation.

In the new facade system installed on the old facade of the building, various materials can be used, including composite panels (or sandwich panels) and metal cassette panels, as shown in Figure 1. Thermal insulation is placed behind the new facade system and attached to the wall of the building using the necessary means of protection from weather influences.

Methods

As a rule, a new facade system involves the installation of an additional frame, which is attached either directly to the old facade, or, preferably, to the floor slabs or load-bearing elements of the building structure. This is better than attaching the frame of a new facade system to a potentially weak old facade. The height of the frame modules is taken from the calculation of the height of the building floor and when installed on the building, the necessary adjustment is made in place, taking into account the irregularities of the existing facade [1].

New metal facade systems have already been installed on many residential and commercial buildings, as well as buildings of educational institutions, in particular in the UK and Scandinavia, according to this principle. Usually, the renovation of the building is carried out in a comprehensive manner and simultaneously with the installation of a new facade system on the old facade of the building, the roof is reconstructed. New windows are also being installed in the building, which significantly increases overall energy savings.

The operational necessity of installing a new facade system on the old facade is largely dictated by the need to significantly increase the thermal insulation of the building, prevent water from entering and removing moisture from the building or the old facade.



Figure 1. Examples of installing new facade systems on old facades of buildings with concrete wall panels. The new facade systems consist of horizontal metal panels

The construction of superstructures and the reconstruction of the roof. "Roof reconstruction" is the creation of a new roof structure on an existing building. Most often, the reasons for the reconstruction of roofs are the poor performance of the existing roof (for example, water leaks) and the desire to use the space under the roof, for example, for utilities or new apartments. The design of the new roof is largely determined by the purpose of the space under it, i.e. whether it will be residential or not. The benefits of having a new space in a building often pay off all the costs of organizing it. During the reconstruction of the roof, lightweight steel frames can be used in the following variants: [2]

- a. Often (closely) located trusses (rafters) between the facade walls;
- b. Rarely located trusses (rafters) between the facade walls and girders resting directly on them;
- c. portal frames or other stable systems supported by columns around the perimeter;
- d. lightweight steel structure supported by a grillage of steel beams supported by individual columns at the bottom.

Farms can be simple pitched (such as Fink or Prat) or attic, giving more usable space. For the construction of superstructures on a building, it is usually best to use lightweight steel structures supported by steel beams that overlap the existing flat or slightly pitched roof as shown in Fig. 2.



Figure 2. Two-storey superstructure made of light steel frame on an existing building, Rotterdam

Modular systems for building renovation. Superstructures on buildings can be easily erected using modular or "volumetric" systems. These systems are self-supporting vertically, but are supported by the existing structure on the sides. As a rule, the modules of these systems have a width of up to 3.6 m, so they are easily transported without special escort and also easily climb buildings. The cladding on the modules can be installed in advance or on site. The best results from the use of such modular systems for building renovation have been achieved in Scandinavia. The popularity of modular systems for building superstructures is steadily growing in the UK and recent examples include medium-sized hotels and social housing projects [3].

Results and Discussion

A. Result

The installation of a new facade system on the old facade assumes very accurate results of the inspection of the exterior walls of the building. This is necessary so that all parts fit exactly in size without the need for on-site refinement. Therefore, a study was conducted on the factors affecting the accuracy of laser scanning. As part of this study, it was necessary to confirm that laser scanning technology is capable of providing sufficient resolution and accuracy of measurement results for the design and production of assembly units of a steel facade system for installation on the old facade of a building. The existing steel facade systems designed for installation on old facades of buildings allow for a deviation in size at the attachment points within 5 mm in all directions. Accordingly, the technologies used to inspect the facade of the building must ensure compliance with these tolerances. The steel cladding panels of the facade system have a smooth, even surface, and any unevenness or curved seam between them will be immediately noticeable to the naked eye[4].

As a rule, buildings requiring renovation in the form of a new facade system are very tall, so manual inspection of their facades is fraught with great difficulties. This problem can be solved by laser scanning technology, which can provide the required accuracy of the results.

B. Discussion

This technology allows you to perform three-dimensional measurements from a certain distance and, provided the results are accurate enough, can be an important tool for collecting data necessary for the design and production of parts of a prefabricated steel facade system for installation on old facades of large buildings.

The accuracy of a high-resolution laser scanning system is determined by a number of factors. Since the defining technical feature of the laser scanning system, which distinguishes it from traditional building inspection tools, is high detail, the following factors can be clearly identified: [5]

- a. Scanning density and spot size (or beam diameter);
- b. interference;
- c. edge effects (distortion at the edges);
- d. Resolution;

- e. Range accuracy;
- f. Angular accuracy;
- g. Surface reflectivity;
- h. Environmental conditions.

Conclusion

The laser scanning system is capable of providing the required level of accuracy at a distance of up to 50 m. Therefore, only the most accurate laser scanning systems are suitable for the inspection of buildings, provided that the working procedure of the study is strictly followed. Scanning accuracy (for example, a grid pitch of 1.5 mm) and spot size (within 5 mm) are considered very important characteristics of the system. Measurement accuracy within 5 mm in all directions is considered sufficient for the design and production of prefabricated steel facade systems.

References

1. R. M. Lawson, R. Podrezki, I. Falkenflet, and S. O. Halved, "Installation of new facade systems on old facades of buildings using light steel structures," Institute of Machine Tool Engineering, R-247, 1999. (Lawson [2] R.M., Podrezki R., Falkenflet I., & Halved S.O., 1999)
2. M. Healer, R. M. Lawson, and M. Gorgolevsky, "Installation of a new roof on an old one using light steel structures," Institute of International Relations, P-246, 1999. (Healer M., Lawson R.M., & Gorgolevsky M., 1999)
3. T. X. Sidikovna and K. M. Erkinovna, "Methods of Designing Preschool Organizations in Urban and Rural Areas," Central Asian Journal of Sanat Va Dizayn, vol. 4, no. 3, pp. 49-52, 2023.
4. H. J. Abdiyev, "The Importance of Furniture in the Interior of Preschool Institutions," British Journal of Global Ecology and Sustainable Development, vol. 5, pp. 94-96, 2022.
5. M. K. Yuldasheva and M. Kamilova, "Foreign Experience in the Design and Construction of Innovative Architecture of Museums of the World," Central Asian Journal of Arts and Design, pp. 320-326, 2023.